


**TECHNICAL INFORMATION**

	IMPERIAL	METRIC
<b>Max Production Width</b>	118.11in	3000mm
<b>Total Thickness</b>	0.11in	2.7mm
<b>Mass</b>	0.57lb/ft <sup>2</sup>	2.8kg/m <sup>2</sup>
<b>Tensile force at 1% elongation (static)</b>	46lbf/in Internal Method - ref. ISO 21181	8N/mm
<b>Working Temp.</b>	+14/+158F <sup>o</sup>	-10/+70C <sup>o</sup>
<b>Flexion (A)</b>	1.57in 40mm	
<b>Counter Flexion (B)</b>	2.36in 60mm	

**COEFFICIENT OF FRICTION** (bottom side) - **Steel** 0.2

**BEST USED FOR**

**GENERAL CHARACTERISTICS**

2 ply white PVC Food approved, low nipple top.

**RECOMMENDED USES**

Slider Bed | Flat Rollers | Incline Conveying |  
 Incline Variation | Slide Bed with Pressure

**SPECIAL CHARACTERISTICS**

- ✓ **Food Approved, FDA compliance**  
acc.to 21 CFR parts 170-19
- ✓ **Food Approved, EU compliance**  
(EC) No. 1935/2004 & (EU) No. 10/2011
- ✓ **Oil & Fat Resistant**

**BELT CONSTRUCTION INFORMATION**

TOP SIDE (Carrying)		TENSION MEMBER		BOTTOM SIDE (Pulley)	
<b>Material</b>	PVC	<b>Interply</b>	PVC	<b>Material</b>	Fabric
<b>Color</b>	White (W)	<b>Weft</b>	Rigid (R)	<b>Color</b>	Fabric (FA)
<b>Thickness</b>	0.05in 1.2mm	<b>Plies</b>	2	<b>Thickness</b>	0in 0mm
<b>Hardness</b> ISO 868	72 Shore A	<b>Fabric</b>	Light Rigid (LR)	<b>Hardness</b> ISO 868	-
<b>Surface</b>	Low Nipple Top (RV)			<b>Surface</b>	PU Impregnated (U0)

\*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.