


F21/K | **PVCEXCON 2F/12 W80 U0/K FA** | **KB2WH8001**

TECHNICAL INFORMATION

	IMPERIAL	METRIC
Max Production Width	78.74in	2000mm
Total Thickness	0.32in	8mm
Mass	0.86lb/ft ²	4.2kg/m ²
Tensile force at 1% elongation (static)	68lb/in Internal Method - ref. ISO 21181	12N/mm
Working Temp.	+14/+158F ^o	-10/+70C ^o
Flexion (A)	4.72in 120mm	
Counter Flexion (B)	7.09in 180mm	

COEFFICIENT OF FRICTION (bottom side) - **Steel** 0.2

BEST USED FOR

GENERAL CHARACTERISTICS

2 ply white PVC Food approved horseshoe top

RECOMMENDED USES

Slider Bed | Flat Rollers | Channel Trough | Conventional Trough | Incline Conveying | Slide Bed with Pressure | Bend Conveyor

SPECIAL CHARACTERISTICS

- ✓ **Food Approved, FDA compliance**
acc.to 21 CFR parts 170-19
- ✓ **Food Approved, EU compliance**
(EC) No. 1935/2004 & (EU) No. 10/2011
- ✓ **Oil & Fat Resistant**

BELT CONSTRUCTION INFORMATION

TOP SIDE (Carrying)		TENSION MEMBER		BOTTOM SIDE (Pulley)	
Material	PVC	Interply	PVC	Material	Fabric
Color	White (W)	Weft	Flexible (F)	Color	Fabric (FA)
Thickness	0.24in 6.2mm	Plies	2	Thickness	0in 0mm
Hardness ISO 868	72 Shore A	Fabric	Flexible (F)	Hardness ISO 868	-
Surface	Horse Shoe (K)			Surface	PU Impregnated (U0)

*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

RELEASED 01/01/2019