


L20/C

PVCCON 2R/12 PG56 00/C

KA2PG5601

TECHNICAL INFORMATION

	IMPERIAL	METRIC
Max Production Width	118.11in	3000mm
Total Thickness	0.22in	5.6mm
Mass	0.78lb/ft ²	3.8kg/m ²
Tensile force at 1% elongation (static)	68lbf/in Internal Method - ref. ISO 21181	12N/mm
Working Temp.	+14/+158F ^o	-10/+70C ^o
Flexion (A)	1.97in 50mm	
Counter Flexion (B)	2.36in 60mm	

COEFFICIENT OF FRICTION (bottom side) - **Steel** 0.24

BEST USED FOR

GENERAL CHARACTERISTICS

2 ply soft green PVC with button top cover.

RECOMMENDED USES

Slider Bed | Flat Rollers | Incline Conveying |
 Incline Variation | Slide Bed with Pressure

SPECIAL CHARACTERISTICS

BELT CONSTRUCTION INFORMATION

TOP SIDE (Carrying)		TENSION MEMBER		BOTTOM SIDE (Pulley)	
Material	PVC	Interply	PVC	Material	Fabric
Color	Petrol Green (PG)	Weft	Rigid (R)	Color	Fabric (FA)
Thickness	0.16in 4mm	Plies	2	Thickness	0in 0mm
Hardness ISO 868	46 Shore A	Fabric	Rigid (R)	Hardness ISO 868	-
Surface	Coin/Button Top (C)			Surface	Bare (00)

*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

RELEASED 01/01/2019

