


L20/H

PVCCON 2R/12 PG85 00/H

KA2PG8501

TECHNICAL INFORMATION

	IMPERIAL	METRIC
Max Production Width	118.11in	3000mm
Total Thickness	0.34in	8.5mm
Mass	1.21lb/ft ²	5.9kg/m ²
Tensile force at 1% elongation (static)	68lb/in Internal Method - ref. ISO 21181	12N/mm
Working Temp.	+14/+158F ^o	-10/+70C ^o
Flexion (A)	2.36in 60mm	
Counter Flexion (B)	4.72in 120mm	

COEFFICIENT OF FRICTION (bottom side) - **Steel** 0.24

BEST USED FOR

GENERAL CHARACTERISTICS

2 ply soft green PVC with staggered sawtooth cover

RECOMMENDED USES

Slider Bed | Flat Rollers | Incline Conveying | Incline Variation | Slide Bed with Pressure

SPECIAL CHARACTERISTICS

BELT CONSTRUCTION INFORMATION



TOP SIDE (Carrying)		TENSION MEMBER		BOTTOM SIDE (Pulley)	
Material	PVC	Interply	PVC	Material	Fabric
Color	Petrol Green (PG)	Weft	Rigid (R)	Color	Fabric (FA)
Thickness	0.26in 6.7mm	Plies	2	Thickness	0in 0mm
Hardness ISO 868	46 Shore A	Fabric	Rigid (R)	Hardness ISO 868	-
Surface	Staggered Saw Tooth (H)			Surface	Bare (00)

*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

RELEASED 01/01/2019