


TECHNICAL INFORMATION

	IMPERIAL	METRIC
Max Production Width	118.11in	3000mm
Total Thickness	0.04in	1.1mm
Mass	0.27lb/ft ²	1.3kg/m ²
Tensile force at 1% elongation (static)	23lb/in Internal Method - ref. ISO 21181	4N/mm
Working Temp.	-13/+194F ^o	-25/+90C ^o
Flexion (A)	0.16in 4mm	
Counter Flexion (B)	0.31in 8mm	

COEFFICIENT OF FRICTION (bottom side) - **Steel** 0.2

BEST USED FOR

GENERAL CHARACTERISTICS

1 ply white PU, antistatic and abrasion resistant. Food Approved

RECOMMENDED USES

Slider Bed | Flat Rollers | Conveyor with Accumulation | Slide Bed with Pressure | Bend Conveyor | Knife Edge Conveyor

SPECIAL CHARACTERISTICS

✓ **Food Approved, FDA compliance**
 acc.to 21 CFR parts 170-19

✓ **Food Approved, EU compliance**
 (EC) No. 1935/2004 & (EU) No. 10/2011

✓ **Antistatic**
 ISO 284 & 21178

✓ **Abrasion Resistant**

✓ **Oil & Fat Resistant**

BELT CONSTRUCTION INFORMATION

TOP SIDE (Carrying)		TENSION MEMBER	BOTTOM SIDE (Pulley)		
Material	PU	Interply	-	Material	Fabric
Color	White (W)	Weft	Rigid (R)	Color	Fabric (FA)
Thickness	0.02in 0.5mm	Plies	1	Thickness	0in 0mm
Hardness ISO 868	88 Shore A	Fabric	Light Rigid (LR)	Hardness ISO 868	-
Surface	Matte Finish (A)			Surface	PU Impregnated (U0)

*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.