


U6/05.05/Z/VR

PVCCON 1R/6 PG20 Z/V05 AS

KA1PG2002

TECHNICAL INFORMATION

	IMPERIAL	METRIC
Max Production Width	118.11in	3000mm
Total Thickness	0.08in	2mm
Mass	0.37lb/ft ²	1.8kg/m ²
Tensile force at 1% elongation (static)	34lbf/in Internal Method - ref. ISO 21181	6N/mm
Working Temp.	+14/+158F ^o	-10/+70C ^o
Flexion (A)	0.79in 20mm	
Counter Flexion (B)	1.18in 30mm	

COEFFICIENT OF FRICTION (bottom side) - **Steel** 0.35

BEST USED FOR

GENERAL CHARACTERISTICS

1 ply double cover PVC green. Inverted pyramid bottom, smooth top.


RECOMMENDED USES

Slider Bed | Flat Rollers | Slide Bed with Pressure

SPECIAL CHARACTERISTICS

- ✓ **Antistatic**
ISO 284 & 21178

BELT CONSTRUCTION INFORMATION



TOP SIDE (Carrying)		TENSION MEMBER		BOTTOM SIDE (Pulley)	
Material	PVC	Interply	PVC	Material	PVC
Color	Petrol Green (PG)	Weft	Rigid (R)	Color	Petrol Green (PG)
Thickness	0.02in 0.5mm	Plies	1	Thickness	0.03in 0.7mm
Hardness ISO 868	74 Shore A	Fabric	Rigid (R)	Hardness ISO 868	74 Shore A
Surface	Smooth - Shiny (L)			Surface	Negative Pyramid (Z)

*Because of continuous development above data is subjected to change without prior notice by Sampla. This data replaces that included in previous publications. Sampla excludes any liability for the incorrect use of the above stated information.

RELEASED 01/01/2019